

Thermoplastic acrylic POLYACRYL, AC-345AR60

Product Description:

This product is a copolymer of acrylic acid and acrylic and methacrylic acid esters.

Technical information:

Characteristics	Range/ Value	Unit	Ref. Standard
Appearance	Viscous Liquid		
Color	colorless /yellow		
Percent Solid	60±1	%	ISO 3251
Acid value	7-11	Mg KOH/g solid	ISO 2114
Viscosity (D6/25°C/50 % AR)	40-50	Sec	ISO 2431

Applications:

This product is recommended for production of traffic paints (mild and cold climates), facades paints and pool paints.

Solubility:

White spirit: partially soluble

Aromatic: soluble

Butyl acetate: soluble

Methyl ethyl ketone: Soluble

Alcohols: needs to be tested.

Head Office: Reef building, boustane saadi boulevard, Isfahan, Iran Plant: 10 St, Razi Industrial zone, 56 Km of Esfahan - Shiraz Road.

Specific characteristics:

- great adherence to the surface

- high hardness
- yellowing resistance.

Miscibility:

- Thermoplastic Acrylic resins
- Thermoplastic nano- composite acrylic resin

Storage:

Keep way from direct sunlight and under 30 °C.

Stability:

Under aforementioned conditions: 9 months from production date.

Tell: (+9831) 36252000 (12 Line) Tell: (+9831) 53323206 - 8

Fax: (+9831) 36612980 Fax: (+9831) 53323210

info@polymeriran.com